

KASPERSKY®




# KASPERSKY SECURITY BULLETIN 2016

GREAT

## CONTENTS

PREDICTIONS FOR 2017: 'INDICATORS OF COMPROMISE' ARE DEAD . . . . .	3
STORY OF THE YEAR: THE RANSOMWARE REVOLUTION.....	22
REVIEW OF THE YEAR .....	42



# PREDICTIONS FOR 2017: 'INDICATORS OF COMPROMISE' ARE DEAD

Our record .....	5
What does 2017 have in store? .....	6
Those dreaded APTs .....	6
The rise of bespoke and passive implants .....	6
Ephemeral infections .....	8
Espionage goes mobile .....	9
The future of financial attacks .....	10
We heard you'd like to rob a bank .....	10
Resilient payment systems .....	11
Dirty, lying ransomware .....	12
The big red button .....	13
The overcrowded internet bites back .....	14
A brick by any other name .....	14
The silent blinky boxes .....	15
Who the hell are you? .....	16
Information warfare .....	16
The promise of deterrence .....	17
Doubling-down on False Flags .....	18
What privacy? .....	19
Pulling the veil .....	19
The espionage ad network .....	20
The rise of the vigilante hacker .....	21

# KASPERSKY SECURITY BULLETIN 2016

## PREDICTIONS FOR 2017: 'INDICATORS OF COMPROMISE' ARE DEAD

Yet another year has flown past and, as far as notable infosec happenings are concerned, this is one for the history books. Drama, intrigue and exploits have plagued 2016 and, as we take stock of some of the more noteworthy stories, we once again cast our gaze forward to glean the shapes of the 2017 threat landscape. Rather than thinly-veiled vendor pitching, we hope to ground these predictions in trends we've observed in the course of our research and provide thought-provoking observations for researchers and visitors to the threat intelligence space alike.



## OUR RECORD

Last year's predictions fared well, with some coming to fruition ahead of schedule. In case you didn't commit these to memory, some of the more notable predictions included:

**APTs:** We anticipated a decreased emphasis on persistence as well as an increased propensity to hide in plain sight by employing commodity malware in targeted attacks. We've seen this, both with an increase in memory or fileless malware as well as through the myriad reported targeted attacks on activists and companies, which relied on off-the-shelf malware like NJRat and Alienspy/Adwind.

**Ransomware:** 2016 can be declared the year of ransomware. Financial malware aimed at victimizing users has practically been galvanized into a ransomware-only space, with the more effective extortion scheme cannibalizing malware development resources from less profitable attempts at victimizing users.

**More Bank Heists:** When we considered the looming expansion of financial crime at the highest level, our hypothetical included targeting institutions like the stock exchange. But it was the attacks on the SWIFT network that brought these predictions to bear, with millions walking out the door thanks to crafty, well-placed malware.

**Internet Attacks:** Most recently, the oft-ignored world of sub-standard Internet-connected devices finally came to bear on our lives in the form of a nasty IoT botnet that caused outages for major Internet services, and hiccups for those relying on a specific DNS provider.

**Shame:** Shame and extortion have continued to great fanfare as strategic and indiscriminate dumps have caused personal, reputational, and political problems left and right. We must admit that the scale and victims of some of these leaks have been genuinely astonishing to us.

## WHAT DOES 2017 HAVE IN STORE?

### Those dreaded APTs

#### The rise of bespoke and passive implants

As hard as it is to get companies and large-scale enterprises to adopt protective measures, we also need to admit when these measures start to wear thin, fray, or fail. Indicators of Compromise (IoCs) are a great way to share traits of already known malware, such as hashes, domains, or execution traits that will allow defenders to recognize an active infection. However, the trendsetting one-percenters of the cyberespionage game have known to defend against these generalized measures, as showcased by the recent [ProjectSauron APT](#), a truly bespoke malware platform whose every feature was altered to fit each victim and thus would not serve to help defenders detect any other infections. That is not to say that defenders are entirely without recourse but it's time to push for the wider adoption of good Yara rules that allow us to both scan far-and-wide across an enterprise, inspect and identify traits in binaries at rest, and scan memory for fragments of known attacks.



ProjectSauron also showcased another sophisticated trait we expect to see on the rise, that of the 'passive implant'. A network-driven backdoor, present in memory or as a backdoored driver in an internet gateway or internet-facing server, silently awaiting magic bytes to awaken its functionality. Until woken by its masters, passive implants will present little or no outward indication of an active infection, and are thus least likely to be found by anyone except the most paranoid of defenders, or as part of a wider incident response scenario. Keep in mind that these implants have no predefined command-and-control infrastructure to correlate and provide a more anonymous beachhead. Thus, this is the tool of choice for the most cautious attackers, who must ensure a way into a target network at a moment's notice.



## Ephemeral infections

While adoption of PowerShell has risen as a dream tool for Windows administrators, it has also proven fruitful ground for the gamut of malware developers looking for stealthy deployment, lateral movement, and reconnaissance capabilities unlikely to be logged by standard configurations. Tiny PowerShell malware stored in memory or in the registry is likely to have a field day on modern Windows systems. Taking this further, we expect to see ephemeral infections: memory-resident malware intended for general reconnaissance and credential collection with no interest in persistence. In highly sensitive environments, stealthy attackers may be satisfied to operate until a reboot wipes their infection from memory if it means avoiding all suspicion or potential operational loss from the discovery of their malware by defenders and researchers. Ephemeral infections will highlight the need for proactive and sophisticated heuristics in advanced anti-malware solutions (see: [System Watcher](#)).



### Espionage goes mobile

Multiple threat actors have employed mobile implants in the past, including [Sofacy](#), [RedOctober](#) and [CloudAtlas](#), as well as customers of HackingTeam and the suspected NSO Pegasus iOS malware suite. However, these have supplemented campaigns largely based on desktop toolkits. As adoption of Desktop OS's suffers from a lack of enthusiasm, and as more of the average user's digital life is effectively transferred to their pockets, we expect to see the rise of primarily mobile espionage campaigns. These will surely benefit from decreased attention and the difficulty of attaining forensic tools for the latest mobile operating systems. Confidence in codesigning and integrity checks has stagnated visibility for security researchers in the mobile arena, but this won't dissuade determined and well-resourced attackers from hunting their targets in this space.



## The future of financial attacks

We heard you'd like to rob a bank...

The announcement of this year's attacks on the SWIFT network caused uproar throughout the financial services industry due to its sheer daring; measured in zeros and commas to the tune of multi-million dollar heists. This move was a natural evolution for players like the [Carbanak gang](#) and perhaps [other interesting threat actors](#). However, these cases remain the work of APT-style actors with a certain panache and established capability. Surely, they're not the only ones interested in robbing a bank for sizable funds?

As cybercriminal interest grows, we expect to see the rise of the SWIFT-heist middlemen in the well-established underground scheme of tiered criminal enterprises. Performing one of these heists requires initial access, specialized software, patience, and, eventually, a money laundering scheme. Each of these steps has a place for already established criminals to provide their services at a fee, with the missing piece being the specialized malware for performing SWIFT attacks. We expect to see the commodification of these attacks through specialized resources being offered for sale in underground forums or through as-a-service schemes.



## Resilient payment systems

As payment systems became increasingly popular and widely adopted, we expected to see greater criminal interest in these. However, it appears that implementations have proven particularly resilient, and no major attacks have been noted at this time. This relief for the consumer may, however, entail a headache for the payment system providers themselves, as cybercriminals are wont to target the latter through direct attacks on the payment system infrastructure. Whether these attacks will result in direct financial losses or simply outages and disruption, we expect increased adoption to attract more nefarious attention.



## Dirty, lying ransomware

As much as we all hate ransomware (and with good reason), most ransomware thrives on the benefit of an unlikely trust relationship between the victim and their attacker. This criminal ecosystem relies on the tenet that the attacker will abide by a tacit contract with the victim that, once payment is received, the ransomed files will be returned. Cybercriminals have exhibited a surprising semblance of professionalism in fulfilling this promise and this has allowed the ecosystem to thrive. However, as the popularity continues to rise and a lesser grade of criminal decides to enter the space, we are likely to encounter more and more 'ransomware' that lacks the quality assurance or general coding capability to actually uphold this promise.


We expect 'skiddie' ransomware to lock away files or system access or simply delete the files, trick the victim into paying the ransom, and provide nothing in return. At that point, little will distinguish ransomware from wiping attacks and we expect the ransomware ecosystem to feel the effects of a 'crisis of confidence'. This may not deter larger, more professional outfits from continuing their extortion campaigns, but it may galvanize forces against the rising ransomware epidemic into abandoning hope for the idea that 'just pay the ransom' is viable advice for victims.



## The big red button

The famous Stuxnet may have opened a Pandora's Box by realizing the potential for targeting industrial systems, but it was carefully designed with a watchful eye towards prolonged sabotage on very specific targets. Even as the infection spread globally, checks on the payload limited collateral damage and no industrial Armageddon came to pass. Since then, however, any rumor or reporting of an industrial accident or unexplained explosion will serve as a peg to pin a cyber-sabotage theory on.

That said, a cyber-sabotage induced industrial accident is certainly not beyond the realm of possibility. As critical infrastructure and manufacturing systems continue to remain connected to the internet, often with little or no protection, these tantalizing targets are bound to whet the appetite of well-resourced attackers looking to cause mayhem. It's important to note that, alarmism aside, these attacks are likely to require certain skills and intent. An unfolding cyber-sabotage attack is likely to come hand-in-hand with rising geopolitical tensions and well-established threat actors intent on targeted destruction or the disruption of essential services.




## The overcrowded internet bites back

### A brick by any other name

Long have we prophesied that the weak security of the Internet of Things (or Threats) will come back to bite us, and behold, the day is here. As the Mirai botnet showcased recently, weak security in needlessly internet-enabled devices provides an opportunity for miscreants to cause mayhem with little or no accountability. While this is no surprise to the infosec-aficionados, the next step may prove particularly interesting, as we predict vigilante hackers may take matters into their own hands.

The notion of patching known and reported vulnerabilities holds a certain sacrosanct stature as validation for the hard (and often uncompensated) work of security researchers. As IoT-device manufacturers continue to pump out unsecured devices that cause wide-scale problems, vigilante hackers are likely to take matters into their own hands. And what better way than to return the headache to the manufacturers themselves by mass bricking these vulnerable devices? As IoT botnets continue to cause DDoS and spam distribution headaches, the ecosystem's immune response may very well take to disabling these devices altogether, to the chagrin of consumers and manufacturers alike. The Internet of Bricks may very well be upon us.



### The silent blinky boxes

The shocking release of the ShadowBrokers dump included a wealth of working exploits for multiple, major manufacturers' firewalls. Reports of exploitation in-the-wild followed not long after as the manufacturers scrambled to understand the vulnerabilities exploited and issue patches. However, the extent of the fallout has yet to be accounted for. What were attackers able to gain with these exploits on hand? What sort of implants may lie dormant in vulnerable devices?

Looking beyond these particular exploits (and keeping in mind the late 2015 discovery of a backdoor in Juniper's ScreenOS), there's a larger issue of device integrity that bears further research when it comes to appliances critical to enterprise perimeters. The open question remains, 'who's your firewall working for?'



## Who the hell are you?

The topic of [False Flags and PsyOps are a particular favorite of ours](#) and to no surprise, we foresee the expansion of several trends in that vein...

### Information warfare

The creation of fake outlets for targeted dumps and extortion was pioneered by threat actors like [Lazarus](#) and [Sofacy](#). After their somewhat successful and highly notorious use in the past few months, we expect information warfare operations to increase in popularity for the sake of opinion manipulation and overall chaos around popular processes. Threat actors interested in dumping hacked data have little to lose from crafting a narrative through an established or fabricated hacktivist group; diverting attention from the attack itself to the contents of their revelations.

The true danger at that point is not that of hacking, or the invasion of privacy, but rather that as journalists and concerned citizens become accustomed to accepting dumped data as newsworthy facts, they open the door to more cunning threat actors seeking to manipulate the outcome by means of data manipulation or omission. Vulnerability to these information warfare operations is at an all-time high and we hope discernment will prevail as the technique is adopted by more players (or by the same players with more throwaway masks).



### The promise of deterrence


As cyberattacks come to play a greater role in international relations, attribution will become a central issue in determining the course of geopolitical overtures. Governmental institutions have some difficult deliberating ahead to determine what standard of attribution will prove enough for demarches or public indictments. As precise attribution is almost impossible with the fragmented visibility of different public and private institutions, it may be the case that 'loose attribution' will be considered good enough for these. While advising extreme caution is important, we must also keep in mind that there is a very real need for consequences to enter the space of cyberattacks. Our bigger issue is making sure that retaliation doesn't engender further problems as cunning threat actors outsmart those seeking to do attribution in the first place. We must also keep in mind that as retaliation and consequences become more likely, we'll see the abuse of open-source and commercial malware begin to increase sharply, with tools like Cobalt Strike and Metasploit providing a cover of plausible deniability that doesn't exist with closed-source proprietary malware.



## Doubling-down on False Flags

While the examples reported in the False Flags report included in-the-wild cases of APTs employing false flag elements, no true pure false flag operation has been witnessed at this time. By that we mean an operation by Threat Actor-A carefully and entirely crafted in the style and with the resources of another, 'Threat Actor-B', with the intent of inciting tertiary retaliation by the victim against the blameless Threat Actor-B. While it's entirely possible that researchers have simply not caught onto this already happening, these sorts of operations won't make sense until retribution for cyberattacks becomes a de facto effect. As retaliation (be it overtures, sanctions, or retaliatory CNE) becomes more common and impulsive, expect true false flag operations to enter the picture.

As this becomes the case, we can expect false flags to be worth even greater investment, perhaps even inciting the dumping of infrastructure or even jealously guarded proprietary toolkits for mass use. In this way, cunning threat actors may cause a momentary overwhelming confusion of researchers and defenders alike, as script kiddies, hacktivists, and cybercriminals are suddenly capable of operating with the proprietary tools of an advanced threat actor, thus providing a cover of anonymity in a mass of attacks and partially crippling the attribution capabilities of an enforcing body.



## What privacy?

### Pulling the veil

There's great value to be found in removing what vestiges of anonymity remain in cyberspace, whether for the sake of advertisers or spies. For the former, tracking with persistent cookies has proven a valuable technique. This is likely to expand further and be combined with widgets and other innocuous additions to common websites that allow companies to track individual users as they make their way beyond their particular domains, and thus compile a cohesive view of their browsing habits (more on this below).

In other parts of the world, the targeting of activists and tracking of social media activities that 'incite instability' will continue to inspire surprising sophistication, as deep pockets continue to stumble into curiously well-placed, unheard of companies with novelties for tracking dissidents and activists through the depth and breadth of the internet. These activities tend to have a great interest in the social networking tendencies of entire geographic regions and how they're affected by dissident voices. Perhaps we'll even see an actor so daring as to break into a social network for a goldmine of PII and incriminating information.



### The espionage ad network


No pervasive technology is more capable of enabling truly targeted attacks than ad networks. Their placement is already entirely financially motivated and there is little or no regulation, as evidenced by recurring malvertising attacks on major sites. By their very nature, ad networks provide excellent target profiling through a combination of IPs, browser fingerprinting, and browsing interest and login selectivity. This kind of user data allows a discriminate attacker to selectively inject or redirect specific victims to their payloads and thus largely avoid collateral infections and the persistent availability of payloads that tend to pique the interest of security researchers. As such, we expect the most advanced cyberespionage actors to find the creation or co-opting of an ad network to be a small investment for sizable operational returns, hitting their targets while protecting their latest toolkits.



### The rise of the vigilante hacker

Following his indiscriminate release of the HackingTeam dump in 2015, the mysterious Phineas Fisher released his guide for aspiring hackers to take down unjust organizations and shady companies. This speaks to a latent sentiment that the asymmetrical power of the vigilante hacker is a force for good, despite the fact that the HackingTeam dump [provided live zero-days to active APT teams](#) and perhaps even encouragement for new and eager customers. As the conspiratorial rhetoric increases around this election cycle, fuelled by the belief that data leaks and dumps are the way to tip the balance of information asymmetry, more will enter the space of vigilante hacking for data dumps and orchestrated leaks against vulnerable organizations.





# STORY OF THE YEAR: THE RANSOMWARE REVOLUTION


Introduction .....	23
Ransomware: the main trends & discoveries of 2016 .....	25
Arrivals and departures .....	26
Abuse of 'educational' ransomware .....	28
Unconventional approaches .....	29
Ransomware in scripting languages .....	30
A long line of amateurs and copycats .....	31
The thriving ransomware economy .....	32
The rise of RaaS .....	32
From commission-based networks to customer support and branding .....	34
It's still all about the Bitcoins .....	34
Ransomware turned its weapons on business .....	35
Ransomware attacks that made the headlines .....	37
Fighting Back .....	38
Through technology .....	38
Through collaboration: The No More Ransom Initiative .....	39
Standing up to ransomware – how to stay safe .....	40
Why you shouldn't pay – advice from the Dutch National High Tech Crime Unit ..	40
Can we ever win the fight against ransomware? .....	41

## INTRODUCTION

In 2016, ransomware continued its rampage across the world, tightening its hold on data and devices, and on individuals and businesses.

### The numbers speak for themselves:

- 62 new ransomware families made their appearance.
- There was an 11-fold increase in the number of ransomware modifications: from 2,900 new modifications in January/March, to 32,091 in July/September.
- At the start of the year, every 20 seconds somebody somewhere was attacked with ransomware – by the end of September, it was one every 10 seconds.
- At the start of the year, every two minutes a business was attacked with ransomware – by the end of September, it was one every 40 seconds.
- One in five small and medium-sized business who paid the ransom never got their data back.



**2016 also saw ransomware grow in sophistication and diversity,** for example: changing tack if it encountered financial software, written in scripting languages, exploiting new infection paths, becoming more targeted, and offering turn-key ransomware-as-a-service solutions to those with fewer skills, resources or time – all through a growing and increasingly efficient underground ecosystem.

**At the same time, 2016 saw the world begin to unite to fight back:**

The [No More Ransom](#) project was launched in July, bringing together the Dutch National Police, Europol, Intel Security and Kaspersky Lab. A further 13 organizations joined in October. Among other things, the collaboration has resulted in a number of free online decryption tools that have so far helped thousands of ransomware victims to recover their data.

**This is just the tip of the iceberg – much remains to be done. Together we can achieve far more than any of us can on our own.**

### What is ransomware?

Ransomware comes in two forms. The most common form of ransomware is the cryptor. These programs encrypt data on the victim's device and demand money in return for a promise to restore the data. Blockers, by contrast, don't affect the data stored on the device. Instead, they prevent the victim from accessing the device. The ransom demand, displayed across the screen, typically masquerades as a notice from a law enforcement agency, reporting that the victim has accessed illegal web content and indicating that they must pay a spot-fine. You can find an overview of both forms of ransomware [here](#).

## RANSOMWARE: THE MAIN TRENDS & DISCOVERIES OF 2016

---

**"Most ransomware thrives on an unlikely relationship of trust between the victim and their attacker: that, once payment is received, the ransomed files will be returned. Cybercriminals have exhibited a surprising semblance of professionalism in fulfilling this promise."**

GReAT, Threat Predictions for 2017

---



Locky  
ransomware  
has so far been  
spread across  
**114**  
countries

## Arrivals and departures

Arrivals: in 2016, the world said hello to Cerber, Locky and CryptXXX – as well as 44,287 new ransomware modifications

Cerber and [Locky](#) arrived in the early Spring. Both are nasty, virulent strains of ransomware that are propagated widely, mainly through spam attachments and exploit kits. They rapidly established themselves as 'major players', targeting individuals and corporates. Not far behind them was CryptXXX. All three families continue to evolve and to hold the world to ransom alongside well-established incumbents such as CTB-Locker, CryptoWall and Shade.

As of October 2016, the top ransomware families detected by Kaspersky Lab products look like this:

	Name	Verdicts*	Percentage of users**
1	CTB-Locker	Trojan-Ransom.Win32.Onion / Trojan-Ransom.NSIS.Onion	25.32
2	Locky	Trojan-Ransom.Win32.Locky / Trojan-Dropper.JS.Locky	7.07
3	TeslaCrypt (active till May 2016)	Trojan-Ransom.Win32.Bitman	6.54
4	Scatter	Trojan-Ransom.Win32.Scatter / Trojan-Ransom.BAT.Scatter / Trojan-Downloader.JS.Scatter / Trojan-Dropper.JS.Scatter	2.85
5	Cryakl	Trojan-Ransom.Win32.Cryakl	2.79
6	CryptoWall	Trojan-Ransom.Win32.Cryptodef	2.36
7	Shade	Trojan-Ransom.Win32.Shade	1.73
8	(generic verdict)	Trojan-Ransom.Win32.Snocry	1.26
9	Crysis	Trojan-Ransom.Win32.Crusis	1.15
10	Cryrar/ACCDFISA	Trojan-Ransom.Win32.Cryrar	0.90

\* These statistics are based on the detection verdicts returned by Kaspersky Lab products, received from users of Kaspersky Lab products who have consented to provide their statistical data.

\*\* Percentage of users targeted by a certain crypto-ransomware family relative to all users targeted with crypto-ransomware.

## Departures: goodbye to Teslascrypt, Chimera and Wildfire – or so it seemed...


Probably the biggest surprise of 2016 was the shutdown of TeslaCrypt and the subsequent release of the master key, apparently by the malware actors themselves.

### TeslaCrypt “committed suicide” – while the police shut down Encryptor RaaS and Wildfire

Encryptor RaaS, one of the first Trojans to offer a Ransomware-as-a-Service model to other criminals shut up shop after part of its botnet was taken down by the police.

Then, in July, approximately 3,500 keys for the [Chimera](#) ransomware were publicly released by someone claiming to be behind the Petya/Mischa ransomware. However, since Petya used some of the Chimera source code for its own ransomware, it could in fact be the same group, simply updating its product suite and causing mischief.

Similarly, [Wildfire](#), whose servers were seized and a decryption key developed following a combined effort by Kaspersky Lab, Intel Security and Europol, now appears to have re-emerged as Hades.



**Ransomware developed for 'education' gave rise to Ded Cryptor and Fantom, among others**

## Abuse of 'educational' ransomware

Well-intentioned researchers developed 'educational' ransomware to give system administrators a tool to simulate a ransomware attack and test their defenses. Criminals were quick to seize upon these tools for their own malicious purposes.

The developer of the educational ransomware [Hidden Tear & EDA2](#) helpfully posted the source code on GitHub. Inevitably, 2016 saw the appearance of numerous malicious Trojans based on this code. This included [Ded Cryptor](#), which changed the wallpaper on a victim computer to a picture of an evil-looking Santa Claus, and demanded a massive two Bitcoins (around \$1,300) as a ransom. Another such program was [Fantom](#), which simulated a genuine-looking Windows update screen.



**Attackers are now targeting back-ups and hard drives – and brute-forcing passwords**

**Shade downloaded spyware if it found financial software**

## Unconventional approaches

- **Why bother with a file when you can have the disk?**

New approaches to ransomware attacks that were seen for the first time in 2016 included disk encryption, where attackers block access to, or encrypt, all the files at once. [Petya](#) is an example of this, scrambling the master index of a user's hard drive and making a reboot impossible. Another Trojan, Dcryptor, also known as Mamba, went one step further, locking down the entire hard drive. This ransomware is particularly unpleasant, scrambling every disk sector including the operating system, apps, shared files and all personal data – using a copy of the open source DiskCryptor software.

- **The 'manual' infection technique**

Dcrypter's infection is carried out manually, with the attackers brute-forcing passwords for remote access to a victim machine. Although not new, this approach has become significantly more prominent in 2016, often as a way to target servers and gain entry into a corporate system.

If the attack succeeds, the Trojan installs and encrypts the files on the server and possibly even on all the network shares accessible from it. We discovered [TeamXRat](#) taking this approach to spread its ransomware on Brazilian servers.

- **Two-in-one infection**

In August we discovered a sample of Shade that had [unexpected functionality](#): if an infected computer turned out to belong to financial services, it would instead download and install a piece of spyware, possibly with the longer term aim of stealing money.

## Ransomware in scripting languages

Another trend that attracted our attention in 2016 was the growing number of cryptors written in scripting languages. In the third quarter alone, we came across several new families written in Python, including HolyCrypt and [CryPy](#), as well as Stampado written in Autolt, the automation language.



**Poor quality ransomware increases likelihood of data being lost forever**

## A long line of amateurs and copycats

Many of the new ransomware Trojans detected in 2016 turned out to be of low-quality; unsophisticated, with software flaws and sloppy errors in the ransom notes.

This was accompanied by a rise in copycat ransomware. Among other things, we spotted that:

- Bart copies the ransom note & the style of Locky's payment page.
- An Autoit-based copycat of Locky (dubbed AutoLocky) uses the same extension ".locky".
- Crusis (aka Crysis) copies the extension ".xtbl" originally used by Shade.
- Xorist copies the whole naming scheme of the files encrypted by Crusis.

Probably the most prominent copycat we discovered this year was [Polyglot](#) (aka MarsJoke). It fully mimics the appearance and file processing approach of [CTB-Locker](#).

These trends are all expected to increase in 2017.

---

**"As the popularity continues to rise and a lesser grade of criminal decides to enter the space, we are likely to encounter more and more 'ransomware' that lacks the quality assurance or general coding capability to actually uphold this promise. We expect 'skiddie' ransomware to lock away files or system access or simply delete the files, trick the victim into paying the ransom, and provide nothing in return."**

GReAT, Threat Predictions for 2017

---

## THE THRIVING RANSOMWARE ECONOMY

**Ransomware  
is increasingly  
for hire on  
the criminal  
underground**

### The rise of RaaS

While Ransomware-as-a-Service is not a new trend, in 2016 this propagation model continued to develop, with ever more ransomware creators offering their malicious product 'on demand'. This approach has proved immensely appealing to criminals who lack the skills, resources or inclination to develop their own.

Notable examples of ransomware that appeared in 2016 and use this model are [Petya/Mischa](#) and [Shark](#) ransomware, which was later rebranded under the name [Atom](#).



# KASPERSKY SECURITY BULLETIN 2016

## STORY OF THE YEAR: THE RANSOMWARE REVOLUTION

This business model is increasingly sophisticated:

The screenshot shows a registration form titled "Registration (Step 1)". It includes fields for "Address (Share)" and "Public key (Share)", both represented by large text input boxes. There is also a checkbox labeled "Enable client-side generation". Below these fields is a "Private key (WIF key)" field, which contains a note about the use of JavaScript for generating addresses. A "Generate" button is located next to this note. At the bottom right of the form is a "Next" button.

First you have to enter a bitcoin address and it's public key. All payments are made on multisig addresses generated from your public key and a public key from us.  
WARNING: It is highly recommended to store the WIF key in a secure place. No one can access your generated bitcoins if you loose that key!

For more informations please check our FAQ, read <https://en.bitcoin.it/wiki/Multisignature> or ask our Support for help.

Address (Share)

Public key (Share)

Enable client-side generation

Private key (WIF key)

This page uses javascript to generate your address within your browser, this means we never receive your private key, this can be independently verified by reviewing the source code. You can even [download](#) the script and host it yourself or run it offline!

Generate

Next

The Petya ransomware partner site

The partner often signs up to a traditional commission-based arrangement. For example, the 'payment table' for Petya ransomware shows that if a partner makes 125 Bitcoins a week they will walk away with 106.25 Bitcoins after commission.

The screenshot shows a table titled "Payment table" with four rows. The columns are "Volume/Week" and "Share". The data is as follows:

Volume/Week	Share
<5 BTC	25%
<25 BTC	50%
<125 BTC	75%
>=125 BTC	85%

Petya payment table

There is also an initial usage fee. Someone looking to use the Stompado ransomware, for example, needs to come up with just \$39.

With other criminals offering their services in spam distribution, ransomware notes etc. it's not difficult for an aspiring attacker to get started.

**Criminals offer customer support to ensure more victims pay**

## From commission-based networks to customer support and branding

The most ‘professional’ attackers offered their victims a help desk and technical support, guiding them through the process of buying Bitcoins to pay the ransom, and sometimes even being open to negotiation. Every step further encouraged the victim to pay.

Further, Kaspersky Lab experts studying ransomware in Brazil noticed that for many attacks, branding the ransomware was a matter of some importance. Those looking for media attention and customer fear would opt for a high profile, celebrity theme or gimmick – while those more concerned about staying under the radar would forgo the temptation of fame and leave their victims facing just an e-mail for contacting the bad guys and a Bitcoin address to pay into.

## It's still all about the Bitcoins

Throughout 2016, the most popular ransomware families still favored payment in Bitcoins. Most ransomware demands were not excessive, averaging at around \$300, although some were charged – and paid – a great deal more.

Others, particularly regional and hand-crafted operations, often preferred a local payment option – although this also meant that they were no longer able to hide in plain sight and blend in with the rest of the ransomware noise.

## RANSOMWARE TURNED ITS WEAPONS ON BUSINESS

**A business is attacked with ransomware every 40 seconds**

In the first three months of 2016, 17% of ransomware attacks targeted corporates – this equates to an attack hitting a business somewhere in the world every two minutes\*. By the end of Q3 this had increased to 23.9% – an attack every 40 seconds.

According to [Kaspersky Lab research](#), in 2016, one in every five businesses worldwide suffered an IT security incident as a result of a ransomware attack.

- [42% of small and medium-sized businesses](#) were hit by ransomware in the last 12 months.
- 32% of them paid the ransom.
- One in five never got their files back, even after paying.
- 67% of those affected by ransomware lost part or all of their corporate data – and one-in-four spent several weeks trying to restore access.

\* Estimates based on: 17% of 372,602 unique users with ransomware attacks blocked by Kaspersky Lab products in Q1, 2016 and 23.9% of 821,865 unique users with ransomware attacks blocked by Kaspersky Lab products in Q3, 2016.



**One in five SMBs never gets their data back, even after paying**

**There is no such thing as a low-risk sector anymore**

Social engineering and human error remain key factors in corporate vulnerability. One in five cases involving significant data loss came about through employee carelessness or lack of awareness.

Some industry sectors are harder hit than others, but our research shows that all are at risk.

	Industry sector	% attacked with ransomware
1	Education	23
2	IT/Telecoms	22
3	Entertainment/Media	21
4	Financial Services	21
5	Construction	19
6	Government/public sector/defence	18
7	Manufacturing	18
8	Transport	17
9	Healthcare	16
10	Retail/wholesale/leisure	16

**"We are seeing more targeted ransomware, where criminal groups carefully hand-pick and spear-phish their targets because of the data they possess and/or their reliance on the availability of this valuable data."**

John Fokker, Digital team Coordinator  
with the Dutch National High Tech Crime unit



## Ransomware attacks that made the headlines

- Hospitals became a prime target – with potentially devastating impact as operations were cancelled, patients diverted to other hospitals and more.
  - The most notorious example of a ransomware attack took place in March when criminals locked down the computers of the [Hollywood Presbyterian Medical Center in Los Angeles](#), until the hospital paid \$17,000.
  - Within weeks, a number of [hospitals in Germany](#) were also hit.
  - In the UK, [28 National Health Service trusts](#) admit to being attacked in 2016.
- Hosted desktop and cloud provider [VESK](#) paid nearly \$23,000 dollars in ransom to recover access to one of its systems following an attack in September.
- Leading media, including the [New York Times, the BBC and AOL](#) were hit by malware carrying ransomware in March 2016.
- [The University of Calgary in Canada](#), a major research center, [acknowledged](#) it had paid around \$16,000 to recover emails that been encrypted for a week.
- A [small police station in Massachusetts](#), ended paying a \$500 ransom (via Bitcoin) in order to retrieve essential case-related data, after an officer opened a poisonous email attachment.
- Even motor racing was hit: a leading [NASCAR racing team](#) faced losing data worth millions to a TeslaCrypt attack in April.

## FIGHTING BACK


**A new free,  
AV-independent  
anti-ransomware  
tool is available**

### Through technology

The latest versions of Kaspersky Lab products for smaller companies have been enhanced with [anti-cryptomalware functionality](#). In addition, a new, free [anti-ransomware tool](#) has been made available for all businesses to download and use, regardless of the security solution they use.

Kaspersky Lab's Anti-Ransomware Tool for Business is a 'light' solution that can function in parallel with other antivirus software. The tool uses two components needed for the early detection of Trojans: the distributed [Kaspersky Security Network](#) and [System Watcher](#), which monitors applications' activity.

Kaspersky Security Network quickly checks the reputation of files and website URLs through the cloud, and System Watcher monitors the behavior of programs, and provides proactive protection from yet-unknown versions of Trojans. Most importantly, the tool can back up files opened by suspicious applications and roll back the changes if the actions taken by programs prove malicious.



**No More Ransom  
has so far got  
4,400 people their  
data back – and  
deprived criminals  
of \$1.5 million in  
ransom**

## Through collaboration: The No More Ransom Initiative

On 25 July 2016, the Dutch National Police, Europol, Intel Security and Kaspersky Lab announced the launch of the [No More Ransom](#) project – a non-commercial initiative that unites public and private organizations and aims to inform people of the dangers of ransomware and help them to recover their data.

The online portal currently carries eight decryption tools, five of which were made by Kaspersky Lab. These can help to restore files encrypted by more than 20 types of cryptomalware. To date, more than 4,400 victims have got their data back – and more than \$1.5 million dollars in ransom demands has been saved.

In October, law enforcement agencies from a further 13 countries joined the project, including: Bosnia and Herzegovina, Bulgaria, Colombia, France, Hungary, Ireland, Italy, Latvia, Lithuania, Portugal, Spain, Switzerland and the United Kingdom.

Eurojust and the European Commission also support the project's objectives, and more partners from the private sector and law enforcement are expected to be announced soon.

---

**"Public/Private partnerships are the essence and the strength of the NMR initiative. They are essential to effectively and efficiently tackle the problem, providing us with much greater capability and reach than law enforcement could have alone."**

Steven Wilson, Head of Europol's EC3

---



## Standing up to ransomware – how to stay safe

1. Back up data regularly.
2. Use a reliable security solution, and remember to keep key features – such as System Watcher – switched on.
3. Always keep software updated on all the devices you use.
4. Treat email attachments, or messages from people you don't know, with caution. If in doubt, don't open it.
5. If you're a business, you should also educate your employees and IT teams; keep sensitive data separate; restrict access; and back up everything, always.
6. If you are unlucky enough to fall victim to an encryptor, don't panic. Use a clean system to check our No More Ransom site; you may well find a decryption tool that can help you get your files back.
7. Last, but not least, remember that ransomware is a criminal offence. Report it to your local law enforcement agency.

## Why you shouldn't pay – advice from the Dutch National High Tech Crime Unit

1. You become a bigger target.
2. You can't trust criminals – you may never get your data back, even if you pay.
3. Your next ransom will be higher.
4. You encourage the criminals.

---

**"We urge people to report an attack. Every victim holds an essential piece of evidence that provides invaluable insight. In return, we can keep them informed and protect them from dodgy third-party 'offers' to unencrypt data. But we need to ensure that more law enforcement offices know how to deal with digital crime."**

Ton Maas, Digital team Coordinator  
with the Dutch National High Tech Crime unit


---



## CAN WE EVER WIN THE FIGHT AGAINST RANSOMWARE?

We believe we can – but only by working together. Ransomware is a lucrative criminal business. To make it stop the world needs to unite to disrupt the criminals' kill-chain and make it increasingly difficult for them to implement and profit from their attacks.





# REVIEW OF THE YEAR

Targeted attacks .....	43
BlackEnergy .....	43
Operation Blockbuster .....	44
Adwind .....	45
Attacks using exploits to the CVE-2015-2545 vulnerability .....	46
Operation Daybreak .....	47
xDedic .....	48
Dropping Elephant.....	49
Operation Ghoul .....	49
ProjectSauron .....	51
Financial threats .....	53
The Internet of things .....	60
Mobile threats .....	66
Rooting malware .....	66
Cybercriminals still using Google Play Store .....	68
Not only Google Play Store .....	71
Bypassing security features .....	71
Mobile ransomware.....	72
Data breaches .....	74
Industrial cyber security: threats and incidents.....	77
Incidents .....	77
Proof-of-Concept PLC based malware .....	79
Zero-days in ICS software and hardware.....	80

## TARGETED ATTACKS

Targeted attacks are now an established part of the threat landscape, so it's no surprise to see such attacks feature in our yearly review.

Here are the major APT campaigns that we reported this year.

**In one massive attack, BlackEnergy disabled power distribution, wiped software and launched a DDoS**

### BlackEnergy

The year started with the developing picture of the BlackEnergy cyber-attack on the Ukrainian energy sector. This attack was unique because of the damage it caused: hackers managed to disable the power distribution system in Western Ukraine, launch a wiper program on targeted systems and conduct a telephone Distributed Denial of Service (DDoS) attack on the technical support services of the affected companies. Kaspersky Lab experts revealed several aspects of the activities of the group responsible for the attack: in particular, [an analysis of the tool used to penetrate the target systems](#). For an overview of the attack, read the [report prepared by the SANS Institute and ICS-CERT](#).



## Operation Blockbuster


Kaspersky Lab was among the participants in [Operation Blockbuster](#), a joint investigation conducted by several major IT security companies into the activities of the Lazarus group (you can read our own report [here](#)). Lazarus is a cybercrime gang — supposedly of North Korean origin — responsible for [the attack on Sony Pictures](#) in 2014. The group has been around since 2009, although its activities ramped up after 2011. Lazarus is responsible for such well-known attacks as Troy, Dark Seoul (Wiper) and WildPositron. The group targeted companies, financial institutions, radio and television.



## Adwind


**Adwind's malware-for-rent had 1,800 customers**

In February, at the [Security Analyst Summit](#), we presented the results of our investigation into [Adwind](#), a cross-platform, multi-functional RAT (Remote Access Tool) distributed through a single Malware-as-a-Platform service. This Trojan has been renamed several times since its first release in 2012 — AlienSpy, Frutas, Unrecom, Sockrat, JSocket and jRat. We believe that between 2013 and 2016 this malware was used in attacks against more than 443,000 individuals, commercial and non-commercial organisations around the world. One of the main features that distinguishes Adwind from other commercial malware is that it is distributed openly as a paid service, where the customer pays a fee in return for use of the malicious software. We estimate that there were around 1,800 customers in the system by the end of 2015. This makes it one of the biggest malware platforms in existence today.



## Attacks using exploits to the CVE-2015-2545 vulnerability

In May, we reported a wave of cyber-espionage attacks conducted by different APT groups across the Asia-Pacific and Far East regions. They all shared one common feature: they exploited the CVE-2015-2545 vulnerability. This flaw enables an attacker to execute arbitrary code using a specially-crafted EPS image file. It uses PostScript and can evade the [Address Space Layout Randomization](#) (ASLR) and [Data Execution Prevention](#) (DEP) protection methods built into Windows. The Platinum, APT16, EvilPost and SPIVY groups were already known to use this exploit. More recently, it was used by the Danti and SVCMONDR groups. You can find an overview of the APTs that use this vulnerability [here](#).



**Over six APT groups used the same vulnerability – patched back in 2015**

One of the most striking aspects of these attacks is that they are successfully making use of a vulnerability that had been patched by Microsoft in September 2015. In our 2016 predictions, [we suggested that APT campaigns would invest less effort in developing sophisticated tools](#) and make greater use of off-the-shelf malware to achieve their goals. This is a case in point: using a known vulnerability, rather than developing a zero-day exploit.

This underlines the need for companies to pay more attention to patch management to secure their IT infrastructure.

**The  
Operation Daybreak  
spying campaign  
by ScarCruft used  
an unknown  
zero-day —  
CVE-2016-1010**


## Operation Daybreak

Of course, there will always be APT groups that seek to take advantage of zero-day exploits. In June, we reported on a cyber-espionage campaign – code-named [Operation Daybreak](#) and launched by a group named ScarCruft – using a previously unknown Adobe Flash Player exploit (CVE-2016-1010). This group is relatively new and has so far managed to stay under the radar. But we think the group might have previously deployed another zero-day exploit (CVE-2016-0147) that was patched in April. The group's targets include an Asian law enforcement agency, one of the world's largest trading companies, a mobile advertising and app monetisation company in the United States, individuals linked to the International Association of Athletics Federations and a restaurant located in one of Dubai's top shopping centres.

While there's no such thing as 100% security, the key is to increase security defences to the point that it becomes so expensive for an attacker to breach them that they give up or choose an alternative target. The best defence against targeted attacks is a multi-layered approach that combines traditional anti-virus technologies with patch management, host intrusion detection and a default-deny whitelisting strategy. According to a study by the Australian Signals Directorate, [85% of targeted attacks analysed could have been stopped](#) by employing four simple mitigation strategies: application whitelisting, updating applications, updating operating systems and restricting administrative privileges.

## xDedic

This year, Kaspersky Lab [investigated an active cybercriminal trading platform, called xDedic](#), an online black market for hacked server credentials around the world — all available through the [Remote Desktop Protocol](#) (RDP). We initially thought that this market extended to 70,000 servers, but new data suggests that the [xDedic market was much wider](#) — including credentials for 176,000 servers. xDedic includes a search engine, enabling potential buyers to find almost anything — from government and corporate networks — for as little as \$8 per server. This low price provides ‘customers’ with access to data on such servers and their use as a bridgehead for further targeted attacks.



**xDedic was the marketplace for at least 70,000 hacked servers — most victims had no idea**

The existence of off-the-shelf underground markets is not new. But we are seeing a greater level of specialisation. And while the model adopted by the xDedic owners isn’t something that can be replicated easily, we think it’s likely that other specialised markets will appear in the future.

**Dropping Elephant showed the fearsome power of high quality social engineering**

## Dropping Elephant

Targeted attack campaigns don't need to be technically advanced in order to be successful. In July, we reported on a group called [Dropping Elephant](#) (also known as 'Chinastrats' and 'Patchwork'). Using a combination of social engineering, old exploit code and some PowerShell-based malware this group was able to steal sensitive data from its victims — high-profile diplomatic and economic organisations linked to China's foreign relations. The attackers use a combination of spear-phishing e-mails and watering-hole attacks. The success of the Dropping Elephant group is striking given that no zero-day exploits or advanced techniques were used to target high-profile victims. In fact, Dropping Elephant provides a clear example of how low investment and use of ready-made toolsets can be very effective when combined with high quality social engineering.

The success of such attacks can be prevented by applying security updates and improving the security awareness of staff.

**Operation Ghoul confirmed that power — with precision-targeted phishing followed by commercial malware**

## Operation Ghoul

The success of social engineering as a means for attackers to gain a foothold in a target organisation was also evident in [Operation Ghoul](#) — the group behind a series of attacks that we reported in June 2016. The attackers sent spear-phishing e-mails with malicious attachments — mainly to top and middle level managers of numerous companies — that appeared to come from a bank in the UAE. The messages claimed to offer payment advice from the bank and included an attached [SWIFT](#) document. But the archive really contained malware. Based on information obtained from the sink-hole of some command and control (C2) servers, the majority of the target organisations work in the industrial and engineering sectors. Others include shipping, pharmaceutical, manufacturing, trading and educational organisations.



The malware used by the Operation Ghoul group is based on the commercial spyware kit Hawkeye, sold openly on the Dark Web. Once installed, the malware collects interesting data from the victim's computer, including keystrokes, clipboard data, FTP server credentials, account data from browsers, messaging clients, e-mail clients and information about installed applications.

The continued success of social engineering as a way of gaining a foothold in target organisations highlights the need for businesses to make staff awareness and education a central component of their security strategy.

## ProjectSauron

In September, we uncovered [ProjectSauron](#), a group that has been stealing confidential data from organisations in Russia, Iran and Rwanda – and probably other countries – since June 2011.



**ProjectSauron changed the landscape forever – an advanced modular spying platform with unique tools for each victim**

The cost, complexity, persistence and the ultimate goal of the operation (i.e. stealing secret data from state-related organisations) suggest that ProjectSauron is a nation-state sponsored campaign. Technical details indicate that the attackers learned from other highly advanced actors, including Duqu, Flame, Equation and Regin – adopting some of their most innovative techniques and improving on their tactics in order to remain undiscovered. All malicious artefacts are customized for each given target, reducing their value as indicators of compromise for any other victim.

### ProjectSauron key features:

1. ProjectSauron is a modular platform designed to enable long-term cyber-espionage campaigns.
2. All modules and network protocols use strong encryption algorithms such as RC6, RC5, RC4, AES, Salsa20, etc.
3. It uses a modified Lua scripting engine to implement the core platform and its plugins.
4. There are upwards of 50 different plugin types.
5. The actor behind ProjectSauron has a high interest in communication encryption software widely used by targeted governmental organizations. It steals encryption keys, configuration files, and IP addresses of the key infrastructure servers related to the encryption software.
6. It is able to exfiltrate data from air-gapped networks by using specially-prepared USB storage drives where data is stored in an area invisible to the operation system.
7. The platform makes extensive use of the DNS protocol for data exfiltration and real-time status reporting.
8. The APT was operational as early as June 2011 and remained active until April 2016.
9. The initial infection vector used to penetrate victim networks remains unknown.
10. The attackers utilize legitimate software distribution channels for lateral movement within infected networks.

The single use of unique methods, such as control server, encryption keys and more, in addition to the adoption of cutting-edge techniques from other major threats groups, is new.

The only effective way to withstand such threats is to deploy multiple layers of security, with sensors to monitor for even the slightest anomaly in organisational workflow, combined with threat intelligence and forensic analysis. You can find further discussion of the methods available to deal with such threats [here](#).

## FINANCIAL THREATS

One of the most direct ways for cybercriminals to make money is by targeting bank customers. Typically, attackers use social engineering to trick their victims into disclosing personal information or installing malware that harvests the personal information (e.g. passwords) used by the victim to access their bank account. In 2016, Kaspersky Lab solutions blocked attempts to launch malware capable of stealing money via online banking on **2,871,965** devices.

However, it's not only bank customers that are targeted by cybercriminals. In recent years we've seen a growing number of attacks on banks and other financial institutions. Probably the best known is [Carbanak](#), which used the infiltration techniques typical of a targeted attack to steal money. This year we have seen further attacks on financial institutions.

**Metel launched targeted attacks on banks — then sent teams to ATMs at night to withdraw the cash**

In February 2016, Kaspersky Lab uncovered the activities of other APT groups targeting financial institutions. The group behind Metel used spear-phishing and browser exploits to infiltrate the corporate network of banks and extend their control to key computers within the bank's IT systems. This level of access gave the attackers the ability to automate the roll-back of ATM transactions: gang members were able to use debit cards to steal money from ATMs without affecting the balance on the card — allowing multiple transactions at different ATMs. Our investigations revealed that the attackers drove around in cars in several Russian cities, stealing money from ATMs belonging to different banks. They worked exclusively at night, stealing money at several locations. We discovered Metel in more than 30 financial institutions, although our incident response team was able to clean the infected networks before major damage could be done. However, the cybercriminals behind Metal are still active and we think that the malware is probably much more widespread.


METEL: KEEP CALM AND ROLL BACK THE TRANSACTIONS



\*ALL NAMES APPEARING IN THIS CHART ARE FICTITIOUS. ANY RESEMBLANCE IS PURELY COINCIDENTAL.

**GCMAN spent  
18 months  
gathering insight  
from infected  
victims before  
attacking – using  
legitimate tools for  
lateral movement**

GCMAN (so-called because the malware is based on code compiled with the GCC compiler) is another example. The group infiltrates financial institutions using spear-phishing e-mails containing a malicious RAR file. When the archive is opened, an executable file is run that leads to the initial infection. Once the group gains a foothold in the organisation, they use legitimate penetration testing tools, such as Putty, VNC and Meterpreter, to gain lateral movement across the organisation until they find strategic computers that they can use to transfer money to e-currency services. The attackers do this by planting a Cron script in one of the bank's servers ([Cron](#) is a time-based scheduler used in Unix-based operating systems) allowing them to complete financial transactions at a rate of \$200 per minute. This script is invoked every minute to post new transactions directly to an upstream payment processing system. Fortunately, the financial institutions detected the suspicious activity, and cancelled the transactions: if they hadn't, the attackers would have successfully transferred money to multiple e-currency services without reporting the transactions to any system within the bank. Kaspersky Lab researchers worked with three financial institutions in Russia that were infected with the GCMAN malware. However, we think that this threat is probably much more widespread.



Interestingly, we learned that the real attack had happened around 18 months before the malware was discovered. The group used an [SQL injection attack](#) on commercial software running on one of the bank's public web servers, and returned a year and a half later to take advantage of the information they had harvested to infiltrate the bank. Two months before this incident, someone had tried different passwords for an admin account on a bank's server: they were very persistent, but confined their attempts only to Saturdays and allowed themselves only three tries per week — all in an effort to stay under the radar of security teams within the target institutions. The activities of the GCMAN group throw light on an emerging trend within the threat landscape — the use of legitimate tools in preference to bespoke malware modules.

Legitimate tools can be just as effective, trigger fewer false alarms and offer a quicker return on investment for the cybercriminals. It's important that IT security teams take account of this when reviewing their corporate security strategy.

You can read further information about the Metel and GCMAN campaigns [here](#).

Of course, banks don't operate in isolation. International money transfers require an inter-bank network, called [SWIFT](#) (Society for Worldwide Interbank Financial Telecommunication).

**Following the theft of \$100 million many banks were forced to improve their authentication and SWIFT software update procedures**

In February 2016, hackers used the SWIFT credentials of Bangladesh Central Bank employees to send fraudulent transaction requests to the Federal Reserve Bank of New York, to transfer millions of dollars to various bank accounts in Asia. The hackers were able to get \$81 million transferred to the Rizal Commercial Banking Corporation in the Philippines and an additional \$20 million to Pan Asia Banking. The loss would have been much greater if there hadn't been a typo in one of the transfer requests — the hackers misspelled the word 'foundation' as 'fandation'. The Federal Reserve Bank noticed the typo and the Bangladesh Bank was able to stop other transactions worth \$850 million. You can read the story [here](#). [Further bank attacks using SWIFT credentials](#) have come to light since the theft from the Bangladesh Bank.

**Insecure ATMs  
became a prime  
target for  
cyberattack**

The group behind Metel was not the only one targeting ATMs. Malware for ATMs is not new, but the number of such malicious programs has been growing in recent years. The most notable, prior to 2016, was [Tyupkin](#), where the attackers gained physical access to the ATM and inserted a bootable CD to take control of the machine.

In May 2016 we reported a new version of the [Skimer](#) ATM malware — this report was the result of an incident response investigation we carried out the previous year. This malware first surfaced in 2009, but has been re-designed — and so too have the tactics of the cybercriminals using it. The new version targets ATMs around the world — we discovered attacks in the UAE, France, the United States, Russia, Macau, China, the Philippines, Spain, Germany, Georgia, Poland, Brazil and the Czech Republic.

Rather than the well-established method of fitting a fake card-reader to the ATM, the attackers take control of the whole ATM. They start by installing the Skimer malware on the ATM — either through physical access or by compromising the bank's internal network. The malware infects the ATM's core — the part of the device responsible for interaction with the wider bank infrastructure, card processing and the dispensing of cash. In contrast to a traditional card skimmer, there are no physical signs that the ATM is infected, leaving the attackers free to capture data from cards used at the ATM (including a customer's bank account number and PIN) or to steal cash directly.

The cybercriminal ‘wakes up’ the infected ATM by inserting a card that contains specific records on the magnetic stripe. After reading the card, Skimer is able to execute a hard-coded command, or receive commands through a special menu activated by the card. The Skimer user interface appears on the display only after the card is ejected and only if the cybercriminal enters the correct session key within 60 seconds. The menu offers 21 different options, including dispensing money, collecting details of cards that have been inserted in the ATM, self-deletion and performing updates. The cybercriminal can save card details on the chip of their card, or print the details it has collected.

The attackers are careful to avoid attracting attention. Rather than take money directly from the ATM – which would be noticed immediately – they wait (sometimes for several months) before taking action. In most cases, they collect data from skimmed cards in order to create cloned cards later. They use the cloned cards in other, non-infected ATMs, casually withdrawing money from the accounts of the victims in a way that can’t be linked back to the compromised ATM.

The upswing in ATM attacks in recent years represents a natural evolution from the more well-established method of using physical skimmers to capture data from cards used in ATMs that have been tampered with. Unfortunately, many ATMs run operating systems with known security weaknesses. This makes physical security even more important.

Kaspersky Lab has several recommendations to help banks protect themselves. They should carry out regular anti-virus scans; employ whitelisting technologies; apply a good device management policy; make use of full disk encryption; password protect the BIOS of ATMs; enforce hard disk booting and isolate the ATM network from the rest of the bank infrastructure. One of our experts provided an [in-depth examination of ATM jackpotting](#) and offered some insights into what should be done to secure these devices.



**New biometric skimmers target next-gen authentication — fingerprint, palm vein, and iris recognition systems**

As you would expect, we don't just investigate attacks that have happened: we also look ahead at emerging technologies and how cybercriminals might try to misuse them. We recently published the results of our investigation into potential methods of authentication — including contactless authentication through [NFC](#), one-time passwords and biometrics. You might be surprised to learn that we discovered 12 manufacturers that are already offering fake fingerprint scanners (i.e. biometric skimmers) and at least three other vendors researching devices to allow criminals to obtain data from palm vein and iris recognition systems. You can find the report [here](#).

## THE INTERNET OF THINGS

**The risk of connecting everything, regardless – in 2016, need we say more?**

These days we're surrounded by smart devices. A growing number of everyday household objects are now smart — telephones, televisions, thermostats, refrigerators, baby monitors, fitness bracelets and even children's toys. Some homes are even designed with the 'smartness' built-in. But it's not just confined to devices around the home: the list of smart devices also includes cars, medical devices, CCTV cameras and parking meters. Ubiquitous Wi-Fi (if not always as ubiquitous as we would like) brings all these devices online, as part of the Internet of things (IoT).

These things are designed to make our lives easier. Since connected everyday objects are able to collect and transfer data automatically, without human interaction, they can operate more effectively and efficiently. However, a world of connected everyday objects means a bigger attack surface for cybercriminals. Unless IoT devices are secured, the personal data they exchange can be compromised, they can be subject to an attack, or they can be used in an attack.

Unfortunately, security features are hard to sell. Connected devices are created by different vendors — in an open market that makes return on investment critical. In a competitive marketplace, things that make customers' lives easier tend to take precedence. In addition, connectivity is often added to a pre-existing communication network that wasn't created with security in mind. So security is often not considered at the design stage — if at all. Historically, security has often been addressed only after something bad has happened to demonstrate the impact of a security weakness.

In the last few years, researchers have highlighted security issues in various connected devices. You may remember that one of our security researchers [investigated his own home](#), to determine whether it was really cyber-secure. Last year, Charlie Miller and Chris Valasek demonstrated how [it was possible to gain wireless access to the critical systems of a Jeep Cherokee](#) – successfully taking control and driving it off the road! Vasilios Hioureas from Kaspersky Lab and Thomas Kinsey from Exigent Systems conducted research into the potential [security weaknesses in CCTV systems](#). More recently a [manufacturer withdrew an insulin pump](#) after discovering that there was a risk of an attacker disabling the device or altering the dosage. There have also been concerns about everyday household objects such as [children's toys](#), [baby monitors](#) and [door-bells](#).

In February, we showed how easy it was to find a hospital, gain access to its internal network and take control of an MRI device — locating personal data about patients and their treatment procedures and obtaining access to the MRI device file system. Our researcher, Sergey Lozhkin, presented his findings at the [Security Analyst Summit](#) this year, highlighting the key factors affecting the security of hospital systems. First, medical devices connected to the Internet were accessible using default passwords. Some were running Windows XP and were susceptible to dozens of old, unpatched vulnerabilities that could be used to compromise hospital systems. Second these medical devices were not segregated from the hospital's local area network. So after obtaining access to one of the hospital's Wi-Fi networks (protected using a weak password), it was possible to get full access to these devices. Third, software architecture vulnerabilities meant that — after connecting to the device and passing through the default login screen — it was possible to access the control interface and personal and diagnostic data about hospital patients. On top of this, there was a command shell implemented in the user interface that provided access to the device's file system. You can read the report [here](#).

## THREAT MODEL: VULNERABILITIES IN MODERN CLINIC INFRASTRUCTURE

### LOCAL NETWORK

- Devices not protected from local network access
- Vulnerability in the application design

### INTERNET OF THINGS – MEDICAL DEVICES

- Connected medical devices in Shodan
- Old and well-known vulnerabilities
- Vulnerability in application design
- Using default passwords

### WI-FI CONNECTION

- Weak password
- Weak connection protocols

### PREVENTION MEASURES:



- Protect access points with strong passwords and authentication protocols
- Fix old and well-known vulnerabilities change default passwords.
- Medical equipment vendors should pay attention to application architecture



### POSSIBLE DAMAGE:



- Medical equipment damage causes damage to patients
- Compromised patient data
- Diagnosis falsification
- Financial damage to clinic due to equipment damage
- Modifications to device firmware and unpredictable operation results

KASPERSKY

© 2016 Kaspersky Lab.  
All rights reserved.

Hospitals should take steps to secure their systems:

- Use strong passwords to protect external connection points.
- Update IT security policies, develop vulnerability assessments and patch systems.
- Protect medical equipment applications in the local network with passwords, in case of unauthorized access to a trusted area.
- Protect infrastructure from malware and hacking attacks with a comprehensive security solution.
- Backup critical information regularly and keep an offline copy.

**Traffic sensor study showed that ‘security-through-obsccurity’ won’t work in a connected world**

In April, we published the results of our research into the traffic sensors that have sprung up in Russian cities and elsewhere over the last few years. These sensors can help to enforce speed limits: drivers' speed camera detectors react to the signals emanating from the new sensors in the same way they do to the radar guns used by traffic police. But that's not why the sensors were installed. They collect raw data about traffic on the roads (the number of cars in each lane, average speed, etc.) and pass it on for analysis by the city authorities.



**Smart cities are complex open ecosystems that need ‘security-by-design’**

Our researcher, Denis Legezo, discovered that the data traffic not protected and can be manipulated. There was no authorization, except that required for Bluetooth, and that was not configured properly. The manufacturer of the road sensors we examined is very generous in its support for service engineers, with a lot of information about the devices publicly available on the manufacturer's official web site and elsewhere.

This is a positive thing. ‘Security through obscurity’ doesn't make a lot of sense: any determined attacker would be able to find out the command system and gain access to the engineering software anyway. So it makes more sense to combine openness, big bounty programs and a fast response to any identified vulnerabilities — if only because the number of researchers will always be bigger than the number of employees in any information security department. You can read the report [here](#).

**Most smart city devices hide their OS behind a public interface — but these carry weaknesses that let attackers in**

Modern cities are complex eco-systems made up of hundreds of different components — including digital ones. The aim of the smart city is to make life more convenient and safe for citizens. But if something can be used, it can also be abused. In September, we presented the findings of our research into various aspects of the smart city. Our researchers, Denis Makrushin and Vladimir Dashchenko, prepared a report, based on their findings, as part of Kaspersky Lab's support for '[Securing Smart Cities](#)' — an international non-profit initiative created to bring together experts in smart city IT security technologies. Ticket terminals in movie theatres, bike rental terminals, service kiosks in government organizations, booking and information terminals at airports and passenger infotainment terminals in city taxis might all have a different appearance, but inside most of them are the same. Each such terminal is either a Windows-based or an Android-based device. The main difference in comparison to ordinary devices is the special kiosk-mode software that runs on public terminals and serves as the user interface. This software provides easy access to specific features of the terminal whilst at the same time restricting access to other features of the device's operating system, including launching a web browser and then virtual keyboard. Accessing these functions provides an attacker with numerous opportunities to compromise the system, as if he was in front of a PC. The research showed that almost any digital public kiosk contains one or multiple security weaknesses which allow an attacker to access hidden features of the OS. You can read the report [here](#).

More and more aspects of everyday life are being made digital. If security isn't considered at the design stage, the potential dangers could be far-reaching — and retro-fitting security might not be straightforward. For a smart city to be safe for the people who live in it, they need to be treated as information systems whose protection requires a custom approach and expertise.

## The Internet was ambushed by kitchen equipment

In October, cybercriminals used a botnet of Internet-connected home devices (such as IP-enabled cameras, DVRs, CCTV cameras and printers) to launch a [DDoS attack against Dyn](#) – a company that provides [DNS](#) services to Twitter, Amazon, PayPal, Netflix and others. The result was that the web sites of these companies went down or worked only intermittently. The attackers infected vulnerable devices with the Mirai malware. This malware had previously been used in a [DDoS attack against the blog site of security researcher Brian Krebs](#) – reputedly the most powerful DDoS attack ever (since the source code for Mirai was recently published online, this doesn't mean that the attack on Dyn was carried out by the same attackers). It's estimated that the Mirai botnet comprises around 550,000 bots. The attackers used default passwords to gain access to online devices. Once the malicious code was written to a device, it became part of the Mirai botnet. As in any DDoS attack, the attackers use the compromised devices to flood their chosen victim's site with traffic, to prevent it operating normally.

This attack, like others that involve compromised IoT devices, exploited the fact that many people don't change the manufacturer's default credentials when they buy a smart device. This makes it easy for attackers to access the device – they simply have to try the known default password. In addition, there are no firmware updates for many devices. IoT devices are also an attractive target for cybercriminals because they often have 24/7 connectivity.

The best advice for anyone using connected/IoT devices at home, is to ensure the default passwords on all devices are changed (using unique, complex passwords) to prevent them being remotely accessed – this includes home routers, which are the gateway to your home network. The temptation may be for people to want to disconnect all devices in the light of such news, but in today's increasingly connected world, that's not realistic; although it's always good to review the functionality of a smart device and disable any functions that you don't actually need. However, good password 'housekeeping' goes a long way to keeping cybercriminals away from your devices. This kind of large scale attack also highlights the need for manufacturers to consider security by design, rather than an afterthought.

## MOBILE THREATS

The main mobile threats in 2016 were advertising Trojans able to use root rights on the infected device. Although obtaining superuser rights isn't new for such malware, in 2016 more and more Android Trojans starting using them, because with such rights they can do everything on the device. In order to gain root rights on a device, Trojans have to exploit vulnerabilities in the system. Since many devices aren't regularly updated, they won't receive the fixes for these vulnerabilities. Because of this, we predict a growth in the number and sophistication of Trojans that use root rights.

Recent updates for the Android system contained not just vulnerability fixes but also new security features — which Trojans quickly found a way to bypass. We expect to see more successful bypassing of new security features in the future. Some of these features may disrupt attacks by the mobile Trojan-Ransom, so their behavior may change in line with this.

### Rooting malware

The most popular and dangerous mobile Trojans in 2016 were [advertising Trojans](#) that can use superuser rights on the device. Most of these came from the Trojan.AndroidOS.Ztorg and Trojan.AndroidOS.Iop families

During 2016 they continue their growth, doubling their presence in the TOP 30 most popular Trojans, when compared with last year (occupying 22 places in 2016, vs. 11 in 2015).


To obtain superuser rights they may use different exploits or existing superuser rights if the device was previously rooted.

They use superuser rights mostly for two things. First of all they may hide themselves in the system folder, which makes their deletion almost impossible. Some of them can even infect the recovery image, which makes it impossible to delete them through a factory reset. Second, they use superuser rights to silently install and launch different apps that aggressively display advertising. Most of these new installed apps are non-malicious apps with ads, but there were several cases where they installed new malware, including the module-based Backdoor.AndroidOS.Triada, [which injects the Zygote](#) process. By doing so, it achieves persistence and can modify SMS sent by other apps to steal the user's money. Using root rights, this Trojan can literally do anything, [including replacing urls](#) in browsers.

**More mobile  
Trojans seized root  
rights — to prevent  
deletion and  
install adware and  
malware**

A device that has been infected with an advertising app is almost unusable, due to the sheer number of annoying ads and installed apps. These Trojans are very hard to delete, and they can silently install and even [buy new apps from Google Play](#).

Mostly, they are spread through third party app stores, but sometimes they are preinstalled on low-cost devices. During this year we saw them distributed through the Google Play Store: on a number of occasions infected apps were installed more than 100,000 times, according to the Google Play statistic. In one instance cybercriminals achieved more than 500,000 installations from Google Play – [they used an infected Pokemon GO Guide app](#), detected as Trojan.AndroidOS.Ztorg.am.



Trojan.AndroidOS.Ztorg.ad in Google Play Store

## Cybercriminals still using Google Play Store

**Malware distributed through Google Play was downloaded hundreds of thousands of times**

Cybercriminals continued to use Google Play Store to spread their malware. During just one week in October, we detected more than ten new apps in the Google Play Store infected by Trojan.AndroidOS.Ztorg.am, a new modification of Trojan.AndroidOS.Ztorg.ad. Many of these new apps had more than 100,000 installations.

The screenshot shows the Google Play Store interface. The top navigation bar includes a back button, a refresh button, a lock icon, the URL <https://play.google.com/store/apps/details?id=com.youtube.video.fun>, and icons for star ratings, file size, and email. Below the bar, the Google Play logo and a search bar with the placeholder 'Search' are visible. A green navigation bar contains the text 'Apps'. To its right are links for 'Categories', 'Home', 'Top Charts', and 'New Releases', along with a magnifying glass icon for search and a gear icon for settings. On the left, a sidebar menu lists 'My apps', 'Shop', 'Games', 'Family', and 'Editors' Choice'. The main content area displays the 'Funny Video Pro' app page. The app's icon features two potatoes with hats. The title 'Funny Video Pro' is in bold. Below it are developer information ('Marsion Tools'), rating ('Everyone'), and a compatibility note ('This app is compatible with your device'). To the right are 'Add to Wishlist' and 'Install' buttons. Two device screenshots are shown below the app details. The first screenshot shows a potato character with a red hat and a pink cloth. The second screenshot shows a list of video thumbnails with titles like 'Fireplace Fairy', 'Halloween: Girl dressed like The Ring', 'Ape with AK-47', 'Pencak Silat', and '3 years old baby angry because he can't eat cupcakes'. A third screenshot on the right shows a message: 'Youtube App is not installed on your device. Install it first before playing the video.' with an 'OK' button. At the bottom of the app page, there is a promotional text: 'Funny Video Pro, funny video playback at will. After installation, watch interesting video, remember to good friends share!'. A 'REVIEWS' section is also present.

Trojan.AndroidOS.Ztorg.am in Google Play Store

**One Android Trojan installed and updated as a clean app before hitting targets with an infected update**

However, not only rooting malware is being distributed through Google Play — Trojans-PSW are too. In October 2015 [we detected Trojan-PSW.AndroidOS.MyVk.a](#) in the Google Play Store. This infected app had more than 100,000 installations and looked like an app for playing music from the VKontakte social network. Nevertheless, it stole users' credentials from this social network. During the year cybercriminals uploaded new modifications of this Trojan to the Google Play Store several times. To bypass security screening, they started to upload a clean app, without any harmful functionality. Then they uploaded a few clean updates and finally, at some stage they uploaded an infected version. They used this algorithm at least twice.


Another example of credential-stealing malware available in the Google Play Store is HEUR:Trojan-Spy.AndroidOS.Instealy.a. These malicious apps were pretending to let users know who has viewed their profile; [but in reality it abused the authentication process](#) to connect to Instagram.

Not only were rooting malware and Trojan-PSW distributed through the Google Play Store. We spotted cybercriminals also using this channel to distribute Trojan-Ransom.AndroidOS.Pletor.d.



Trojan-Ransom.AndroidOS.Pletor.d in Google Play Store

Originally, the Trojan-Ransom.AndroidOS.Pletor family encrypted user files on the infected device, but this modification only blocks the infected device and asks the user for money. It is interesting that Pletor was created by the same cybercriminal group that created the mobile banking Trojan [Aceland](#). In December 2015, this group used the Google Play Store to distribute Trojan-Downloader.AndroidOS.Aceland.b — a Trojan that downloads and installs Trojan-Banker.AndroidOS.Aceland.a.



A Trojan-Downloader.AndroidOS.Aceland.b page in Google Play Store

Trojans were  
also distributed  
through  
advertising  
networks

## Not only Google Play Store

While advertising Trojans used exploits after infection to obtain superuser rights, there were a few cases where malware used exploits for distribution.

Our colleagues from Bluecoat [detected](#) Trojan-Ransom.AndroidOS.Fusob distributed by exploits. The exploit kit was able to download and install malicious apps. Some time later [we detected](#) cybercriminals trying to use well-known vulnerabilities to distribute malware.

Another interesting way to infect users was used to distribute Trojan-Banker.AndroidOS.Svpeng. In this case, the cybercriminals [used the Google AdSense](#) advertising network to distribute Trojan-Banker.AndroidOS.Svpeng.q. Svpeng can steal information about the user's bank cards [via phishing windows](#), and intercept, delete and send text messages. Distributing through one of the most popular online advertising networks allowed Svpeng to become the most popular Android banking Trojan in 2016. In addition, it became the second most popular Trojan overall after rooting Trojans.

## Bypassing security features

As mentioned above, in 2016, some Trojans found new ways to bypass some Android security features.

Recent versions of the Android OS ask for the user's approval when an SMS is sent to a premium number. The Tiny SMS Trojan overlays this dialog with its own screen without covering the buttons in the original window.


The same technique was used by Trojan-Banker.AndroidOS.Asacub. In [this case](#) the Trojan overlays the regular system window with its own window, containing buttons, and requests device administrator privileges. The Trojan thereby conceals the fact that it is gaining elevated privileges in the system from the user, and tricks the user into approving these privileges. Furthermore, the Asacub Trojan acquired SMS messenger functionality and started to offer its services in place of the device's standard SMS app. This allows the Trojan to bypass system constraints first introduced in Android 4.4 as well as delete or hide from the user any incoming SMSs.

In June 2016, [we detected](#) a new modification of Trojan-Banker.AndroidOS.Gugi with the capability to bypass two new security features added in Android 6: permission-based app overlays and a dynamic permission requirement for dangerous in-app activities such as SMS or calls. The modification does not use any vulnerabilities, just social engineering.

The Gugi and  
Asacub Trojans  
found ways round  
new Android  
security features

## Mobile ransomware

The most popular Trojan-Ransom in 2016 was [Trojan-Ransom.AndroidOS.Fusob](#). It was most actively distributed in Germany, the United States and the United Kingdom and will not work in CIS and some neighbouring countries. The criminals usually demand between \$100 and \$200 to unblock the device. The ransom has to be paid in the form of codes from pre-paid iTunes cards. This Trojan saw a huge rise in popularity between November 2015 and March 2016: with the number of users attacked increasing 12-fold over that time, but then its popularity fell to almost the same number of attacked users as in the previous year.



Number of unique users attacked by Trojan-Ransom.AndroidOS.Fusob

While there are more users attacked by mobile bankers than there are those attacked by mobile ransoms, the opposite is seen in the number of collected installation packets: starting from Q2 2016 we see a higher number of Trojan-Ransoms than Trojan-Bankers.

**Mobile ransomware overlays rather than encrypts data as it's often backed-up**

While the first mobile Trojan-Ransom encrypted user files and demanded money for their decryption, most modern Trojan-Ransoms for Android do not encrypt user files. They just show their window over all other apps, overlapping even system dialogs. Mobile encryptions are so unpopular mainly because user data on the mobile device is usually backed-up on cloud services. Regular Trojan-Ransoms that overlap all other windows with their own window also works well and it is very hard to get rid of such a Trojan.

One of the most popular mobile ransom families in China — Trojan-Ransom.AndroidOS.Congur — blocks the infected device in another way: it asks for Device Administrators rights after the start and then changes the pin code or sets one up (if there was no pin code before). It asks the user to contact cybercriminals via QQ messenger to find out the new device pin code. This method is very simple but still effective.

Trojan-Ransom is one of the technologically simplest and most effective Trojans. That is why we expect them to continue their growth and to see more new Trojan-Ransom families next year.



## DATA BREACHES

Personal information is a valuable commodity, so it's no surprise that cybercriminals target online providers, looking for ways to bulk-steal data in a single attack. We've become accustomed to the steady stream of security breaches reported in the media. This year has been no different, with data leaks at [beautifulpeople.com](#), [Tumblr](#), the [nulled.io](#) hacker forum (underlining the fact that it's not just legitimate systems that are targeted), [Kiddicare](#), [VK.com](#), [Sage](#), the [official forum of DotA 2](#), [Yahoo](#), [Brazzers](#), [Weebly](#) and [Tesco Bank](#).

Some of these attacks resulted in the theft of huge amounts of data, highlighting the fact that many companies are failing to take adequate steps to defend themselves. It's not simply a matter of defending the corporate perimeter.

There's no such thing as 100% security, so it's not possible to guarantee that systems can't be breached, especially when a breach occurs with help from an insider or where someone on the inside is tricked into doing something that jeopardises corporate security.

But any organisation that holds personal data has a duty of care to secure it effectively. This includes hashing and salting customer passwords and encrypting other sensitive data.

Consumers have no direct control over the security of the personal data they disclose to online providers. But they can limit the damage of a security breach at an online provider by ensuring that they choose passwords that are unique and complex: an ideal password is at least 15 characters long and consists of a mixture of letters, numbers and symbols from the entire keyboard. If this seems like a daunting task, you can find [useful tips on how to create secure – but easy to remember – passwords](#). As an alternative, you could use a password manager application to handle all this for you automatically.

**The theft of  
LinkedIn data  
revealed a million  
accounts with the  
password '123456'**

Unfortunately, all too often people use easy-to-guess passwords and re-use the same password for multiple online accounts — so that if the password for one is compromised, all the victim's online IDs are vulnerable. This issue was highlighted publicly in May 2016 when a hacker known as 'Peace' attempted to sell [117 million LinkedIn e-mails and passwords](#) that had been stolen some years earlier. More than one million of the stolen passwords were '123456'.

In July, we took [a look back at the impact of the Ashley Madison breach](#), one year after the attack that led to the leak of customer data, offering some good tips to anyone who might be considering looking online for love (and good advice for managing any online account).

The issue of passwords is one that keeps surfacing. If we choose a password that is too easy to guess, we leave ourselves wide open to identity theft. The problem is compounded if we recycle the same password across multiple online accounts. This is why many providers, including Apple, Google and Microsoft, now offer two-factor authentication — i.e. requiring customers to enter a code generated by a hardware token, or one sent to a mobile device, in order to access a site, or at least in order to make changes to account settings. Two-factor authentication certainly enhances security — but only if it's required, rather than just being an option.

Given the potential impact of a security breach, it's hardly surprising to see regulatory authorities paying closer attention to the issue. The UK Information Commissioner's Office (ICO) recently issued a [record fine of £400,000 to TalkTalk](#) for the company's 'failure to implement the most basic cyber security measures', related to the attack on the company in October 2015. In the view of the ICO, the record fine 'acts as a warning to others that cyber security is not an IT issue, it is a boardroom issue'.

The EU General Data Protection Regulation (GDPR), which comes into force in May 2018, will require companies to notify the regulator of data breaches, with significant fines for failure to secure personal data. You can find an overview of the regulation [here](#). It's to be hoped that this will ensure that companies report breaches in a timely fashion. This issue was thrown into sharp relief this year after [Dropbox sent a notification to many of its customers requiring them to change their passwords](#). The security breach at Dropbox in 2012 resulted in the leaking not only of e-mail addresses, but passwords too. Dropbox notified customers about e-mail addresses — but not passwords — at the time. Fortunately, the passwords were hashed and salted and Dropbox offers two-step verification.

Several companies are hoping to replace passwords altogether. Apple allows fingerprint authorization for iTunes purchases and payments using Apple Pay. Samsung has said it will introduce fingerprint, voice and iris recognition for Samsung Pay. Amazon has announced 'selfie-pay'. MasterCard and HSBC have announced the introduction of facial and voice recognition to authorise transactions. The chief benefit, of course, is that it replaces something that customers **have to remember** (a password) with something they **have** — with no opportunity to short-circuit the process (as they do when they choose a weak password).

**Authentication beyond passwords is a major issue for security**

Biometrics are seen by many as the way forward. However, they are not a security panacea. Biometrics can be spoofed, as we've discussed before ([here](#), [here](#) and [here](#)); and biometric data can be stolen. It would be more helpful to see biometrics as a replacement for usernames, rather than passwords. In the end, multi-factor authentication is essential — combining something you know, something you have and something you are.

## INDUSTRIAL CYBER SECURITY: THREATS AND INCIDENTS

We can't call 2016 a remarkable year in terms of the number or criticality of cyber-security incidents in industrial environment. Nevertheless there were several interesting cases we'd like to highlight in the report.

### Incidents

This year we've heard twice about cyber security issues in nuclear power plants. The first time it happened was at the end of April when the operator company of the Gundremmingen nuclear power plant [reported](#) about the Kido (aka Conficker) worm infection discovered in the computers of the unit B control system. This control system is a part of the nuclear fuel rods loading machine. Fortunately, the worm did not affect the technological process and didn't damage the power plant.

The relevant supervisory authority and the German Federal office for information security (BSI) have been informed. All critical systems and devices were checked, and no other signs of malicious infection were found. As the result of the incident, security measures have been extended. The incident was classified according to the German reporting criteria in category N (Normal). According to the international scale for assessment of events (INES), it is classified to level zero (below scale, no or very low safety significance).

The source of infection has not been disclosed, but the press officer of the Nuclear Power Plant has said that about 18 USB removable devices used in the office network were found infected with same Kido worm. He said that no damage could be inflicted because all critical control systems of the power plant are decoupled and the whole system architecture is redundant to denial-of-service and safe from manipulation.

Although, in this case the Kido infection did not cause any serious damage (fortunately), it is silly to think that only targeted and specifically designed malware could. At the very end of 2015, the [Ukrainian power distribution substations were hit by a highly coordinated cyber attack](#). The adversaries sent phishing emails containing exploit to individuals in the administrative or IT network of the electricity companies. As soon as the first computers were infected, adversaries found their way into the OT network and managed to disrupt the power supply. And, what is important in this case, they cut off all remote access to the grid network. By wiping specific engineering software and corrupting the system's boot sectors, the adversaries made it impossible for the system to be managed and repaired remotely.

The idea here is that even if malware does not affect a technological process, but causes denial-of-service of critical supporting systems such as SCADA, OPS gateway, remote access, etc. – the ICS will probably continue to work according to its latest settings, but there would be no way to control and correct the process in case of accident or emergency.

**ICS attacks that are not communicated to the security industry can't be analysed and nothing is learned**

Months ago, Yukiya Amano, the head of the International Atomic Energy Agency (IAEA), [revealed](#) that a nuclear power plant was attacked by hackers about 2-3 years ago. Amano said that 'This actually happened and it caused some problems. While the plant did not have to shut down, it needed to take some precautionary measures'. But, it's not just a problem of a cyber-security issue causing some disruption on a power plant. Obviously, it's also the bigger problem of absence of communication and transparency between ICS and cyber security communities. At the end of the day, cyber security specialists have no chance to analyze the issue and ICS owners and vendors could not proactively implement mitigation measures.

## Proof-of-Concept PLC based malware

This August, a proof-of-concept PLC worm was presented at the Black Hat 2016 conference by researchers from OpenSource Security team. The worm written solely as a PLC program is capable of autonomously identifying programmable logic controllers (PLC) in the network and spread from one PLC to another. It is also able to manipulate PLC input and output, cause denial-of-service of a PLC, connect to command and control servers and serve as a proxy for attack propagation.

The most interesting part of the proof-of-concept (PoC) is the techniques used to infect a PLC. The PoC was written for Siemens S7-1200 controllers which have the access protection feature. This feature, if turned on, allows for the password required to access the PLC using the S7CommPlus protocol to be set. Thus, it prevents any unauthorized actor from reading and modifying the code on the PLC. But, by default, the access protection is turned off. If the feature is turned on than the only way for a worm to infect the PLC is to either brute force the password or to steal/hijack it somehow.

On the other hand, if the access protection feature is turned off, there are still two other protection mechanisms, designed to limit access to the PLC:

- Know-how protection which forbids extraction and modifications of the PLC program from a device
- Copy protection that prohibits the duplication of the PLC program to another PLC device.

The access verification for both protection mechanisms – ‘Know-how Protection’ and ‘Copy protection’ – was implemented client side (within the TIA portal), which means that a simple self-written tool can read and write blocks on the PLC bypassing the authentication checks. Siemens published the [advisory](#) and provided the patch for S7-1200 firmware.

The important lesson here is that any rough device or threat actor with access to an ICS network could easily compromise whole control systems. Moreover, the PLC devices are more vulnerable to attack (especially DoS) because it doesn’t expect anyone except SCADA or engineering software to communicate with it, so there is little to no protection against unauthorized access, bad input or malicious manipulations.

## Zero-days in ICS software and hardware

According to [US ICS CERT data](#) in the fiscal year 2015 fiscal (from October 2015 to September 2016) they received 427 vulnerability reports, compared to 245 vulnerability reports received during the previous year. About 25% of those vulnerabilities are due to improper input validation and 27% – due to poor access controls. Other significant category of vulnerabilities – configuration and operational ones – are often disclaimed by vendors. The vulnerabilities such as default credentials, default security settings (which are often switched off), hidden API or undocumented functionality are very dangerous because they do not require high technical skills while providing extensive access into a control system.

### The gap between reporting an ICS vulnerability and the issue of a patch is often too long

The sad news is that it takes an enormously long time between a vulnerability report being sent to a vendor and a patch being provided. Sometimes it never happens, because a vendor [claims the vulnerable product is discontinued](#). From the standpoint of an ICS owner it results in undertaking a huge cost for modernization or a huge risk of being compromised.

In conclusion, we want to highlight the importance of contributing to ICS cyber security by communities of security researchers. For the last few years we have seen a remarkable growth in interest in ICS security topics. A significant number of research reports as well as tools and frameworks are published each year. For example, earlier this year we published our own review of [Industrial cybersecurity threat landscape](#). It allows cyber security specialists from other (not ICS) fields to quickly jump in and contribute their experience and knowledge.



[Securelist](#), the resource for Kaspersky Lab experts' technical research, analysis, and thoughts.

Follow us



[Kaspersky Lab global Website](#)



[Eugene Kaspersky Blog](#)



[Kaspersky Lab B2C Blog](#)



[Kaspersky Lab B2B Blog](#)



[Kaspersky Lab security news service](#)



[Kaspersky Lab Academy](#)